

Hi -Torque Clamps



HTM HI-TORQUE CLAMPS		
PART NO.	DIAM. RANGE (mm)	
	FROM	TO
HTM200	31	54
HTM250	44	68
HTM300	57	79
HTM350	69	92
HTM400	82	104
HTM450	95	117
HTM500	107	130
HTM550	120	142
HTM600	133	155
HTM650	146	168
HTM700	158	181
HTM750	171	193
HTM800	184	206
HTM850	196	219
HTM900	209	231



HTM HI-TORQUE CLAMPS - EXTENDED RANGE		
PART NO.	DIAM. RANGE (mm)	
	FROM	TO
HP2	31	66
HP3	53	107
HP4	102	155
HP5	155	231

Withstands more than 4 times the SAE torque requirements for worm-drive clamps. $5/8$ " wide $302/304$ half hard stainless steel band. Eight screw-threads are engaged in the band simultaneously for incredible torquing drive (over 200in. lbs), sealing pressure and vibration resistance.

** All of the above are sold in box quantities of 10 per box.*

Recommended torque rating in FT.LBS (for malleable iron and stainless steel clamps only)

Single Bolt Superclamps



**Boxed quantities only.*

SINGLE BOLT SUPERCLAMPS			
PART NO.	FOR HOSE O.D. (mm)		TORQUE IN / LBS
	FROM	TO	
SC019	17	19	31
SC022	20	22	31
SC025	23	25	31
SC028	26	28	31
SC031	29	31	53
SC035	32	35	53
SC039	36	39	53
SC043	4	43	53
SC047	44	47	106
SC051	48	51	106
SC055	52	55	106
SC059	56	59	106
SC063	60	63	106
SC067	64	67	106
SC073	68	73	168
SC079	74	79	168
SC085	80	85	168
SC091	86	91	168
SC097	92	97	168
SC103	98	103	168
SC112	104	112	168
SC121	113	121	168
SC130	122	130	168
SC139	131	139	332
SC148	140	148	332
SC161	149	161	332
SC174	162	174	332
SC187	174	187	332
SC200	188	200	332
SC213	201	213	332
SC226	214	226	332
SC239	227	239	332
SC252	240	252	332

- Carbon Steel Band CW15 (DIN 1-114 1).
- Finish: Zinc Plated Chromate / Passivated.
- Torque Values are recommended in in/lbs.

C