

Fixed & Swivel Flanged Smooth Tails EN 14420-2 (formally DIN 2817)



FIXED FLANGED HOSE SPIGOTS X TAIL

PART NO.	SIZE	MATERIAL
FF25/CS	DN25	Carbon Steel
FF32/CS	DN32	Carbon Steel
FF40/CS	DN40	Carbon Steel
FF50/CS	DN50	Carbon Steel
FF65/CS	DN65	Carbon Steel
FF80/CS	DN80	Carbon Steel
FF100/CS	DN100	Carbon Steel
FF25/SS	DN25	Stainless Steel
FF32/SS	DN32	Stainless Steel
FF40/SS	DN40	Stainless Steel
FF50/SS	DN50	Stainless Steel
FF65/SS	DN65	Stainless Steel
FF80/SS	DN80	Stainless Steel
FF100/SS	DN100	Stainless Steel

D



SWIVEL FLANGED HOSE SPIGOTS X TAIL

PART NO.	SIZE	MATERIAL
FS25/CS	DN25	Carbon Steel
FS32/CS	DN32	Carbon Steel
FS45/CS	DN40	Carbon Steel
FS50/CS	DN50	Carbon Steel
FS65/CS	DN65	Carbon Steel
FS80/CS	DN80	Carbon Steel
FS100/CS	DN100	Carbon Steel
FS125/CS	DN125	Carbon Steel
FS150/CS	DN150	Carbon Steel
FS200/CS	DN200	Carbon Steel
FS25/SS	DN25	Stainless Steel
FS32/SS	DN32	Stainless Steel
FS40/SS	DN40	Stainless Steel
FS50/SS	DN50	Stainless Steel
FS65/SS	DN65	Stainless Steel
FS80/SS	DN80	Stainless Steel
FS100/SS	DN100	Stainless Steel

These flanges have PN16 PCD drilling, other flanges including specials are available upon request. Please note: PN10 and PN16 dimensions are the same up to DN150. Stainless steel units are produced from 316. Carbon steel are zinc plated for protection. This range of flanged spigots come complete with a smooth hose tail and retaining collar suitable for use with our range of safety clamps.