

Spiral Guard™ Flame Retardant Hose and Cable Protection



Provides heavy duty hose, cable or wire protection. Used in mining, quarrying, forestry, offshore industries and most hydraulic hose applications.

- Crush and high abrasion resistance
- Chemical and UV ray resistant
- Self-lubricating to reduce hose wear
- Easy to install on-site
- Smooth radius on all edges
- Can be used on single or multiple hose bundles

FLAME RETARDANT PRODUCT

- Approved by MSHA 1C-231/1
- Flame retardant and self extinguishing
- Temperature Range: -148°F to 212°F, (-100°C to 100°C)

PART NO.	SPIRAL GUARD I.D.*		COIL LENGTH	1	2	MULTI SPIRAL
	(inches)	(mm)	(m)	WIRE	WIRE	HOSE
FRSGX16	1/2"	13	20	#4	#4	-
FRSGX20	5/8"	16	20	#6	#4	#6
FRSGX25	3/4"	19	20	#8	#8	#8
FRSGX32	15/16"	24	20	#12	#10	#12
FRSGX40	1 1/4"	32	20	#16	#16	#16
FRSGX50	1 1/2"	38	20	#20	#20	#20
FRSGX63	1 15/16"	49	20	#32	#24	#24
FRSGX75	2 3/8"	60	20	-	#32	#32
FRSGX90	2 5/8"	67	20	-	-	-
FRSGX110	3 3/16"	81	10	-	-	-

STANDARD PRODUCT

- Not flame retardant
- Temperature Range: -58°F to 194°F, (-50°C to 90°C)

PART NO.	SPIRAL GUARD I.D.*		COIL LENGTH	1	2	MULTI SPIRAL
	(inches)	(mm)	(m)	WIRE	WIRE	HOSE
NFSGX16	1/2"	13	20	#4	#4	-
NFSGX20	5/8"	16	20	#6	#4	#6
NFSGX25	3/4"	19	20	#8	#8	#8
NFSGX32	15/16"	24	20	#12	#10	#12
NFSGX40	1 1/4"	32	20	#16	#16	#16
NFSGX50	1 1/2"	38	20	#20	#20	#20
NFSGX63	1 15/16"	49	20	#32	#24	#24
NFSGX75	2 3/8"	60	20	-	#32	#32
NFSGX90	2 5/8"	67	20	-	-	-
NFSGX110	3 3/16"	81	10	-	-	-

FOR INSTALLATION & SAFETY GUIDELINES REFER TO THE TECHNICAL SECTION

Fire Jackets for Hose



Used to protect hose and hose assemblies, tubing, piping, wiring and cables from high temperatures or molten splash. Will also help maintain line temperature and reduce environmental overheating and overcooling.

- Resistant to hydraulic fluids and lubricating oil
- Colour is iron oxide red
- Supplied in 50' lengths, (not continuous)
- Temperature Range: -65°F to 500°F (-54°C to 260°C)
- Sleeving slides easily over hose and expands to go over fittings
- Compounded silicone rubber coating over fiberglass
- Completely non-asbestos

FIRE JACKET		
PART NO.	NOMINAL I.D.	
	(inches)	(mm)
0610-4		
1010-6	1/2"	13
1310-8	5/8"	16
1610-10	3/4"	19
1910-12	15/16"	24
2210-14	1 1/4"	32
2510-16	1 1/2"	38
3210-20	1 5/16"	49
3810-24	2 3/8"	60
4510-28	2 5/8"	67
5110-32	3 3/16"	81

Dixon Diameter Tape



- 6' tape for quickly finding the outside diameter of any cylindrical object
- Converts circumference to O.D. at the measured point
- Metal case

DIAMETER TAPE	
PART NO.	
DDT1	

FOR INSTALLATION & SAFETY GUIDELINES REFER TO THE TECHNICAL SECTION