


## PD-Series ISO15171-1 Diagnostic Interchange

- Couplings provide no-spill connection/disconnection for pressure diagnostic applications
- PD-Series couplers and nipples are fully compliant with the parameters outlined in ISO15171-1
- Couplers have an automatic push-to-connect sleeve for easy connection and disconnection
- Plated steel construction provides optimum corrosion resistance



PERFORMANCE SPECIFICATIONS	OPERATING bar (psi)	COUPLED BURST bar (psi)	FLOW RATE ΔP=5 bar	LOCKING MECHANISM
1/8" Steel	414 (6,000)	1,655 (24,000)	3 LPM (0.80 GPM)	10 Balls


'PD' SERIES INTERCHANGE	PARKER	AEROQUIP	TOMCO	FASTER
1/8" Steel	PD-Series	FD90	Series DK	Series DF



(Female Thread)

### PD-SERIES ISO15171-1 DIAGNOSTIC INTERCHANGE (COUPLER)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
1PDF1	1/8"	1/8"-27 NPTF	Steel
1PDF2	1/8"	1/4"-18 NPTF	Steel



(Female Thread)

### PD-SERIES ISO15171-1 DIAGNOSTIC INTERCHANGE (NIPPLE)


PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
PD1F1	1/8"	1/8"-27 NPTF	Steel
PD1F2	1/8"	1/4"-18 NPTF	Steel



(Male Thread)

### PD-SERIES ISO15171-1 DIAGNOSTIC INTERCHANGE (COUPLER)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
1PDM2	1/8"	1/4"-18 NPTF	Steel



(Male Thread)

### PD-SERIES ISO15171-1 DIAGNOSTIC INTERCHANGE (NIPPLE)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
PD1M1	1/8"	1/8"-27 NPTF	Steel
PD1M2	1/8"	1/4"-18 NPTF	Steel
PD10M2	1/8"	7/16"-20 ORB	Steel
PD10M3	1/8"	9/16"-18 ORB	Steel