


## NK-Series Japanese Industrial Interchange

- Fully interchangeable with Japanese Industrial couplers, automatic or manual sleeve, and nipples
- Couplers have a 'One Touch' automatic sleeve to provide convenient automatic push-to-connect engagement
- Couplers and nipples are constructed of steel with chrome-over-nickel plating



PERFORMANCE SPECIFICATIONS	OPERATING bar (psi)	BURST bar (psi)	FLOW ΔP=0.4 bar (6.9 bar inlet)	LOCKING MECHANISM
1/4"	34 (500)	138 (2,000)	38 CFM	4 Balls
'NK' SERIES INTERCHANGE	NITTO KOHKI	RECTUS	CEJN	-
1/4"	Hi Cupla 200	Series 13	Series 314	-



(Female Thread)

### NK-SERIES JAPANESE INDUSTRIAL INTERCHANGE (AUTOMATIC COUPLER)


PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2NKF2	1/4"	1/4"-18 NPTF	steel
2NKBF2	1/4"	G1/4" BSPP	steel



(Female Thread)

### NK-SERIES JAPANESE INDUSTRIAL INTERCHANGE (UNVALVED NIPPLE)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
NK2F2	1/4"	1/4"-18 NPTF	steel
NK2BF2	1/4"	G1/4" BSPP	steel



(Male Thread)

### NK-SERIES JAPANESE INDUSTRIAL INTERCHANGE (AUTOMATIC COUPLER)


PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2NKM2	1/4"	1/4"-18 NPTF	steel
2NKBM2	1/4"	R1/4" BSPT	steel



(Male Thread)

### NK-SERIES JAPANESE INDUSTRIAL INTERCHANGE (UNVALVED NIPPLE)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
NK2M2	1/4"	1/4"-18 NPTF	steel
NK2BM2	1/4"	R1/4" BSPT	steel



(Standard Hose Barb)

### NK-SERIES JAPANESE INDUSTRIAL INTERCHANGE (AUTOMATIC COUPLER)

PART NO.	BODY SIZE	BARB CONFIGURATION	BODY MATERIAL
2NKS2	1/4"	1/4" Hose Barb	brass



(Standard Hose Barb)

### NK-SERIES JAPANESE INDUSTRIAL INTERCHANGE (UNVALVED NIPPLE)

PART NO.	BODY SIZE	BARB CONFIGURATION	BODY MATERIAL
NK2S2	1/4"	1/4" Hose Barb	brass