


## CL-Series 'PCL' Interchange

- High flow valving system provides maximum flow capability while minimising pressure drop
- Coupler ball placement, in combination with steel nipples, reduces incidents of brinelling during operation
- CL-Series couplings offer improved side load performance over standard pneumatic couplings
- Wide variety of end configurations ensures compatibility in a variety of applications/installations
- Automatic couplers offer the convenience of 'push-to-connect' coupling



PERFORMANCE SPECIFICATIONS	OPERATING bar (psi)	MIN. BURST bar (psi)	FLOW RATE $\Delta P=0.4$ BAR (6.9 BAR INLET)	LOCKING MECHANISM
1/4"	34 (500)	138 (2,000)	33 CFM	4 Balls

'CL' SERIES INTERCHANGE	PCL AIRFLOW	RECTUS	CEJN	-
1/4"	AIRFLOW	RECTUS 19KA	CEJN 295	-



(Female Thread)

### CL-SERIES 'PCL' INTERCHANGE (AUTOMATIC COUPLER)


PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2CLBF2	1/4"	G1/4" BSPP	Steel
2CLBF3	1/4"	G3/8" BSPP	Steel



(Female Thread)

### CL-SERIES 'PCL' INTERCHANGE (NIPPLE)


PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
CL2BF2	1/4"	G1/4" BSPP	Steel
CL2BF3	1/4"	G3/8" BSPP	Steel



(Male Thread)

### CL-SERIES 'PCL' INTERCHANGE (AUTOMATIC COUPLER)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2CLBM2	1/4"	R1/4" BSPT	Steel
2CLBM3	1/4"	R3/8" BSPT	Steel



(Male Thread)

## CL-SERIES 'PCL' INTERCHANGE (NIPPLE)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
CL2BM2	1/4"	R1/4" BSPT	Steel
CL2BM3	1/4"	R3/8" BSPT	Steel



(Hose Barb)

## CL-SERIES 'PCL' INTERCHANGE (AUTOMATIC COUPLER)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2CL2S2	1/4"	1/4" Hose Barb	Steel
2CL2S3	1/4"	3/8" Hose Barb	Steel



(Hose Barb)

## CL-SERIES 'PCL' INTERCHANGE (NIPPLE)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
CL2S2	1/4"	1/4" Hose Barb	Steel
CL2S3	1/4"	3/8" Hose Barb	Steel