

## "Boss" Ground Joint Seal Couplings

- Sizes:** 1/4" to 6"
- Materials:** Plated Steel and/or Malleable Iron, Stainless Steel and Brass
- Pressure:** Maximum working pressure 600 psi (using "Boss" clamps at correct torque setting)
- Details:** "Boss" Non-Metallic Polymer Seat (U.S. Patent No. 5, 577, 777) is not subject to corrosion and offers resistance to chemicals and steam found in manufacturing facilities. A precision machined recess holds the seat firmly in place, allowing it to absorb harsh punishment. Recommended for steam service up to 450°F (232°C); easy to seal; works with existing "Boss" Ground Joint Stems.
- Use only with genuine "Boss" Clamps made in U.S.A.



**"BOSS" COMPLETE COUPLING**

PART NO.	SIZE	THREAD	MATERIAL
GF1*	1/4"	BSP PL/NPT	Plated Steel/Malleable Iron
GF3*	3/8"	BSP PL/NPT	Plated Steel/Malleable Iron
GF6	1/2"	BSP PL/NPT	Plated Steel/Malleable Iron
GF26	3/4"	BSP PL/NPT	Plated Steel/Malleable Iron
GF36	1"	BSP PL/NPT	Plated Steel/Malleable Iron
GF51	1 1/4"	BSP PL/NPT	Plated Steel/Malleable Iron
GF61	1 1/2"	BSP PL/NPT	Plated Steel/Malleable Iron
GF81**	2"	BSP PL/NPT	Plated Steel/Malleable Iron
GF96	2 1/2"	BSP PL/NPT	Plated Steel/Malleable Iron
GF111	3"	BSP PL/NPT	Plated Steel/Malleable Iron
GF141	4"	BSP PL/NPT	Plated Steel/Malleable Iron
GF201*	6"	BSP PL/NPT	Plated Steel/Malleable Iron
RGF26	3/4"	BSP PL/NPT	316 Stainless Steel
RGF36	1"	BSP PL/NPT	316 Stainless Steel
RGF51	1 1/4"	BSP PL/NPT	316 Stainless Steel
RGF61	1 1/2"	BSP PL/NPT	316 Stainless Steel
RGF 81	2"	BSP PL/NPT	316 Stainless Steel
BGF26	3/4"	BSP PL/NPT	Brass
BGF36	1"	BSP PL/NPT	Brass
BGF51	1 1/4"	BSP PL/NPT	Brass
BGF61	1 1/2"	BSP PL/NPT	Brass
BGF81	2"	BSP PL/NPT	Brass

\* GF1, GF3, GF201, are supplied with Copper Seat Spuds.

\*\* GF81 are not to be used with #250 or #306 "Boss" Clamps.